

Exhibit A

Description

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a Continuation-in-Part of U.S. application Ser. No. 11/999,570, filed on Dec. 7, 2007, which is incorporated herein by reference in its entirety.

~~BACKGROUND OF THE INVENTION~~~~1. Field of the Invention~~

The present ~~specification~~disclosure is generally ~~directed~~related to a digital media communication protocol structured to facilitate transferring and/or transmitting one or more digital media files to and/or from a media terminal and a media node via at least one interactive computer network.

~~2. Background~~Description of the Related Art

As technology continues to develop and play a significant role in today's society, a vast majority of portable devices, including mobile telephones, cellular telephones, portable MP3 players, handheld or portable game consoles, Personal Digital Assistants ("PDA"), etc. are equipped with memory devices, such as hard drives and/or removable flash or memory cards, which are capable of holding or storing large amounts of data and or digital media files including digital photographs, videos, audio/music files, etc. Accordingly, with the advent of such devices having these capabilities, individuals or users are more inclined to carry around their media files, such as, for example, digital photo albums, family videos, and/or favorite music tracks.

The drawback to the above noted portable media devices, however, is that many of the devices include relatively small display screens, some of which display poor quality photos and/or videos. In addition, the speakers associated with the corresponding portable device(s) are typically rather small and produce minimal or poor sound therefrom.

In addition, the individuals or users of the media devices may desire to share the digital media files and/or transfer, display, or play the files on a computer or other media device equipped with a larger or better quality screen, or having higher quality speakers than that disposed on the portable device(s). In addition, some media devices may have better editing software, or have access to the World Wide Web to further distribute the digital media files.

Accordingly, it would be advantageous if the digital media communication protocol of the present specification is structured to facilitate transferring or transmitting one or more digital media files between two or more media devices, such as a media terminal and/or a media node, via at least one interactive computer network. In particular, it would be beneficial if the digital media communication protocol includes a communication link structured to bypass at least one or more security measures, such as a password and/or firewall, employed by the interactive computer network, the corresponding networking devices, and/or the particular media devices themselves.

In addition, once the communication link is established it would be particularly beneficial if the various media devices, including the media terminal(s) and/or media node(s), are structured to display, save, edit, manipulate, and/or transfer the one or more digital media files.

~~SUMMARY~~

~~The present specification is directed to a digital media communication protocol having at least one media terminal and at least one media node. In particular, the media terminal of at least one embodiment includes a computer, including but not limited to a desktop computer, mobile or laptop computer, PDA, cellular telephone, etc., and is disposed in an accessible relation to one or more interactive computer networks. In at least one embodiment, the media node includes, but is in no way limited to, a portable device such as, for example, a mobile computer, PDA, cellular telephone, handheld game console, portable MP3 player, etc. In yet another embodiment,~~

~~however, the media node includes a desktop computer or other like device. Furthermore, the interactive computer network of the present specification may include any one or more computer networks, including home, office, private, and/or limited networks, as well as access to the World Wide Web, for example, via the Internet.~~

~~In addition, at least one embodiment of the present system includes a wireless range structured to permit authorized access to the one or more interactive computer networks. Moreover, the media node(s) is disposable within the wireless range, wherein the media node is detectable by the media terminal disposed in accessible relation to the interactive computer network. The present specification further includes a communication link initiated by the media terminal and structured to dispose the media terminal and the media node in a communicative relation with one another via the interactive computer network.~~

~~Once the communication link is established, the media terminal and the media node are structured to transmit at least one digital media file therebetween via the communication link. In particular, the media terminal and/or media node is structured to display, save, edit, manipulate, and/or transfer or send the digital media file.~~

~~These and other objects, features and advantages of the present system will become more clear when the drawings as well as the detailed description are taken into consideration.~~

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

For a fuller more complete understanding of the nature of the present system disclosure, reference should be had to the following detailed description taken in connection with the accompanying drawings in which:

FIG. 1 is a schematic representation of one embodiment of the digital media communication protocol in accordance with the present specification.

FIG. 2 is a schematic representation of another embodiment of the digital media communication protocol in accordance with the present specification.

FIG. 3 is a schematic representation of yet another embodiment of the digital media communication protocol in accordance with the present specification.

FIG. 4 is a partial flow chart of at least one illustrative implementation of the digital media communication protocol of the present specification. FIG. 1 is a schematic representation of at least one embodiment of the system for enabling social interactive wireless communication as disclosed in accordance with the present disclosure.

Like reference numerals refer to like parts throughout the several views of the drawings.

DETAILED DESCRIPTION

As shown in the accompanying drawings, the present specification relates to a digital media communication protocol, generally indicated as **10**. As illustrated in FIGS. 1 through 3, at least one embodiment of the present protocol or system **10** includes one or more media terminals **20** and one or more media nodes **30**. In particular, the media terminal(s) **20** of at least one embodiment is disposed in an accessible relation to at least one interactive computer network **40** and may include, for example, a computer processing device **22**, an input device **24**, and a display device **26**. Accordingly, as shown in FIG. 1, the media terminal(s) **20** of the various embodiments described herein may include a ~~desktop~~ computer, however, any device structured to facilitate the practice of the present system in the intended fashion may be utilized, including but in no way limited to a desktop computer, laptop or notebook computer, PDA, video game console, mobile telephone, media system of a vehicle (e.g., an automobile), etc.

The media node(s) **30** of at least one embodiment of the present system **10** generally includes a portable device such as a cellular or mobile telephone, PDA, portable mp3 player, laptop or

notebook computer, or any other digital media device structured to facilitate the practice of the present system in the intended manner. In at least one embodiment, however, the media node **30** is not limited to a portable device, and may include a more stationary device or structure such as, for example, a desktop computer.

Furthermore, the various embodiments of the present specification include at least one interactive computer network **40**, **40'**. In particular, as illustrated in FIG. 1, at least one embodiment includes one or more home, office, private, limited, or closed interactive computer networks **40** at least partially defined by one or more networking devices **42**, including but not limited to a router, access point, and/or switch. Accordingly, the interactive computer network **40** may include a Local Area Network ("LAN"), Wide Area Network ("WAN"), Private Area Network ("PAN"), peer-to-peer network, near field communication ("NFC"), Bluetooth network, etc. As best shown in FIGS. 2 and 3, it is also contemplated that, especially wherein the interactive computer network **40** is a Bluetooth or peer-to-peer network, the media terminal(s) **20** and/or the media node(s) **30** can function as the networking device(s) **42**, at least to the extent of defining the interactive computer network **40**. Additionally, and referring again to FIG. 1, at least one interactive computer network **40'** of at least one embodiment includes access to the World Wide Web, for example via the Internet. Such access to the World Wide Web **40'** may be facilitated in any manner, including but not limited to, via a cable or DSL modem **44**, as shown in FIG. 1, or via one or more satellites **46** and/or one or more towers or base stations **48**, as illustrated in FIG. 2.

In addition, and still referring to FIGS. 1 through 3, at least one embodiment of the present system **10** includes a wireless range **50** structured to permit access to the one or more interactive computer networks **40**. In particular, as shown in FIG. 1, the wireless range **50** may be at least partially defined by networking devices **42**, such as a wireless router, access point, switch, etc. In yet another embodiment, as shown in FIGS. 2 and 3, however, the wireless range **50** may be partially defined by the media terminal **20** and/or media node **30**, such as, for example, wherein the interactive computer network **40** includes a Bluetooth or peer-to-peer network.

In addition, and as an attempt to minimize or eliminate unauthorized access or security breaches to the interactive computer network **40**, the interactive computer network **40** and/or the various networking device(s) **42** may include one or more networking device security measures **41** including a firewall, and/or passwords/keys such as, for example, Wi-Fi Protected Access ("WPA") keys, and/or Wireless Application Protocol ("WAP") keys. Accordingly, only authorized individuals or computers may generally have access to the interactive computer network **40** through the firewall, via use of the password(s)/key(s), and/or any other networking device security measure(s) **41**.

The present system **10** further includes at least one digital media file **60** initially disposed or saved on at least one of the media terminal(s) **20** or media node(s) **30**. Specifically, the digital media file(s) **60** may be disposed on the media terminal(s) **20**, the media node(s) **30**, or both. However, it should be apparent that for purposes of the present system **10**, the digital media file **60** need not necessarily be created or originated on either the media terminal(s) **20** or the media node(s) **30**. In particular, the digital media file(s) **60** may include virtually any electronic file or data such as a digital photograph, video, audio, animation, text, or any other electronic document or object.

Moreover, in at least one embodiment of the present system **10**, the media node(s) **30** is disposable within the wireless range **50**, wherein the media node **30** is detectable by the media terminal **20**. In particular, as stated above, in at least one embodiment, the media

node **30** includes a portable device, such as a mobile or cellular phone, PDA, laptop, etc. Accordingly, the media node **30** may be disposed within, i.e., enter, the confines of the wireless range **50**, for example, when a user or individual carries the media node **30** therein. In addition, for purposes of the present system **10**, the media node **30** may be disposed within the wireless range **50** when the device is powered on, activated, or otherwise configured into a discoverable and/or detectable state while simultaneously being physically disposed within the confines of the wireless range **50**, and as such, the media node **30** need not necessarily be portable or easily movable. For instance, while physically disposed within the confines of the wireless range **50**, the media node(s) **30** may be powered on or otherwise have wireless or Bluetooth capabilities activated.

Furthermore, the media terminal(s) **20** disposed in accessible relation to the interactive computer network **40** are structured to detect the media node(s) **30** as the media node(s) **30** is disposed within the confines of or is otherwise detectable within the wireless range **50**. Particularly, in at least one embodiment, each media node **30** includes a node identifier structured to distinguish one media node **30** within the wireless range **50** from another. For example, the node identifier may include a device name, model/serial number, Media Access Control (“MAC”) address, or Internet Protocol (“IP”) address. Accordingly, as the media node **30** enters or is otherwise disposed within the wireless range **50**, the media terminal **20** is structured to detect and/or identify the media node **30**, for example, by the corresponding node identifier.

In addition, at least one embodiment of the present system **10** includes a terminal program disposed in an accessible relation to the media terminal **20**. In particular, the terminal program of at least one embodiment is a computer software program structured to facilitate the practice of the present system **10** in the intended fashion, at least from the media terminal **20** side of the system **10**. The terminal program, of at least one embodiment, may be disposed on the media terminal **20**, such as, for example, on a hard drive, or other memory device associated with the media terminal **20**. In yet another embodiment, however, the terminal program may be accessible via the at least one interactive network **40**, **40'**, such as, for example, via the World Wide Web. For example, in the embodiment wherein the terminal program is accessible via the World Wide Web, a user may direct a web browser disposed in the media terminal **20** to a particular web site, which then runs or executes the terminal program and/or downloads the terminal program to the media terminal **20**.

Either way, the terminal program may include at least one script which is structured to consistently or periodically monitor the wireless range **50** associated with the interactive computer network **40** for the existence of media nodes **30**. When a media node **30** is disposed within the wireless range **50**, the terminal program may be structured or configured to automatically alert a user at the media terminal **20** of the existence or detection of the media node **20**. In particular, the terminal program may deploy a pop-up display, play an audio alarm or tone, etc. On the other hand, the terminal program may be structured or configured to alert or notify the user of any detected media nodes **30** only upon the user's specific instructions. For example, the media terminal **20**, and in particular the terminal program thereof, may be structured to list or display the media nodes **30** currently disposed within the wireless range **50** upon the user clicking on or otherwise manipulating a corresponding option of the terminal program.

At least one embodiment of the present system **10** further includes a communication link **70** structured to dispose the media terminal(s) **20** and the media node(s) **30** in a communicative relation with one another via the interactive computer network **40**. In particular,

the communication link 70 of the various embodiments of the present system 10 is ~~initiated or created and/or~~ requested by the media terminal 20. As stated above, the media terminal 20 is structured to detect the media node(s) 30 disposed within the wireless range 50. As also stated above, the media node 30 may, but need not, however, be configured to have access to the interactive computer network 40. For example, the interactive computer network 40 and/or the corresponding networking device(s) 42 may be equipped with one or more security measures 41, including a WEP key or other password. The media node 30 may, but need not have access to the WEP key or other security measure 41 so as to access the corresponding interactive computer network 40. Even so, the media terminal 20 is structured to create and/or initiate a communication link 70 with the one or more detected media nodes 30 disposed within the wireless range 50, for example, by sending and/or transmitting a request to the corresponding media node(s) 30 to establish a communication link 70 therewith via the interactive computer network 40. As illustrated in FIG. 1, the media terminal 20 need not be disposed within the wireless range 50 in order to detect the media nodes 30 or to create and/or initiate a communication link 70 therewith. In at least one embodiment of the present system 10, the media terminal 20 does, however, need to be disposed in an accessible relation with the interactive computer network 40, for example, wirelessly or via a direct cable 43. More in particular, the communication link 70 of at least one embodiment of the present specification is structured to bypass one or more media terminal security measures 21, media node security measures 31, and/or networking device security measures 41. Moreover, the security measures 21, 31, 41 may includes passwords, keys, firewalls, etc. structured to minimize or eliminate unauthorized access to the corresponding media terminal 20, media node 30, networking device(s) 42, and/or interactive computer network 40, 40'. Referring again to FIG. 1, in the embodiment wherein the interactive computer network 40 and the wireless range 50 are at least partially defined by networking device(s) 42, such as a router, access point, or switch, once established, the communication link 70 is structured to be disposed between the media terminal 20 and the media node 30, and through the corresponding networking device(s) 42. Particularly, in at least one implementation of the present system 10, because the media terminal 20 is disposed in an accessible relation to the interactive computer network 40, and because the communication link 70 is created and/or initiated by the media terminal 20, the communication link 70 can be established regardless of whether the corresponding media node 30 independently has access to the interactive computer network 40. In addition, the initiation of the communication link 70 by the media terminal 20, such as through a request to establish a communication link 70, at least partially allows the communication link 70 to bypass the firewall or other media terminal security measure(s) 21.

Moreover, the media terminal 20 of at least one embodiment of the present system 10 may be structured or configured to automatically create and/or initiate a communication link 70 with the detected media nodes 30. However, more practically, a user in control of the media terminal 20 may direct the media terminal 20 to create and/or initiate the communication link 70 with one or more selected media node(s) 30, for example, via the terminal program. Similarly, the media node 30 may be structured or configured to automatically accept or decline creation of the communication link 70 initiated by the media terminal 20. However, in at least one embodiment of the present system 10, the media node(s) 30 may be structured or configured for a user in control of the media node 30 to selectively accept or decline the creation or establishment of a communication link 70 initiated by the corresponding media terminal 20. As such, in at least one embodiment, the media node 30 includes one or more node programs

structured to facilitate the practice of the present system **10** in the intended fashion, at least from the media node **30** side of the system **10**.

Once the communication link **70** is initiated, accepted, and/or ultimately established between the media terminal **20** and the media node **30**, the digital media file(s) **60** may be selectively transmitted therebetween. In particular, if the digital media file **60** is initially disposed on the media node **30**, the media node **30** and the media terminal **20** may cooperatively communicate via the communication link **70** such that the digital media file **60** may be transmitted from the media node **30** to the media terminal **20**. In addition, the converse is also true. Particularly, if the digital media file **60** is disposed on the media terminal **20**, the media node **30** and the media terminal **20** may cooperatively communicate via the communication link **70** such that the digital media file **60** may be transmitted from the media terminal **20** to the media node **30**. Furthermore, in at least one embodiment of the present system **10**, the device on which the digital media file **60** is initially disposed, such as the media node **30** or the media terminal **20**, is structured to “push” the digital media file **60** to the receiving device **20, 30** via the communication link **70**. Similarly, in at least one embodiment, once the communication link **70** is established, the receiving device **20, 30** is structured to “pull” the digital media file **60** from the transmitting device **30, 20** via the communication link **70**.

For illustrative purposes only, the communication link **70**, the terminal program, and/or the node program may be structured to include a selective set of parameters which define or limit the permissions associated with the communication link **70**. In particular, in at least one embodiment, the selective set of parameters may include the option of transmitting the digital media file **60** via the communication link **70** merely for purposes of displaying and/or playing the digital media file **60**, saving the digital media file **60**, manipulating or otherwise editing the digital media file **60**, etc. In the various embodiments of the present system **10**, it is contemplated that these parameters may be selected from either the media terminal **20** or the media node **30**, at various times. For instance, the parameters may be selected by the media terminal **20**, or a user in control thereof, when the communication link **70** is created and/or initiated, or by either the media terminal **20** or the media node **30** when the communication link **70** is accepted or created.

Furthermore, it is contemplated that the protocol **10** of the present system includes a plurality of versions of the terminal program and/or the node program, stated and described above. For instance, at least one embodiment includes at least one limited version of the terminal and/or node programs and at least one full version of the programs. It is contemplated that the limited versions of the terminal and/or node programs are distributed at no cost or at least a lower cost than the corresponding full versions, and as such, provide limited functionality. Of course, the terminal and/or node programs, whether the limited and/or full versions, may come pre-installed with the corresponding media terminal **20** or media node **30**.

Moreover, for illustrative purposes only, FIG. 4 shows one implementation of the system **10** in accordance with the present specification, generally indicated as **100**. In particular, and as above, in at least one embodiment, the media node **30** may include a portable device, such as for example, a mobile phone, a cellular telephone, PDA, or mobile computer. For purposes of the illustrative implementation of FIG. 4, the interactive computer network **40** includes a wireless range **50** located in one or more offices or rooms, wherein the media terminal **20** is also disposed within one of the offices or rooms in accessible relation to the interactive computer network **40**. Furthermore, the digital media file **60** of the present illustrative implementation of FIG. 4 may be disposed on the media node **30**, whereas the user in control of the media node **30** desires to

display the digital media file **60** on the display device **26** of the media terminal **20**. For example, a user of a wireless mobile device (i.e., an example of a media node **30**) can use the wireless mobile device to control the display of a digital media file **60** on a display (i.e., an example of display device **26**) of a vehicle media system (i.e., an example of a media terminal **20**) within an automobile. The vehicle media system may be part of a vehicle navigation system. Alternatively, the vehicle media system may include one or more displays within the vehicle that are separate from the vehicle navigation system. In another aspect, the vehicle media system includes an audio system (e.g., the radio) of the vehicle.

As shown in FIG. 4, the media node **30** may be disposed within the wireless range **102**. For example, the user in control of, and/or having possession of, the media node **30** may walk into the office which is disposed within the wireless range **50**. As stated above, once the media node **30** is disposed within the wireless range **50**, as shown at **104**, the media terminal **20** is structured to detect the media node **20**. The media terminal **20** may then create and/or initiate a communication link **70** between the media terminal **20** and the media node **30** via the interactive computer network **40**, as shown at **106**, for instance, by sending a request thereto. The media node **30** may then accept the request by the media terminal **20**, which establishes the communication link **70**, as illustrated at **108** in FIG. 4. Once the communication link **70** is established, the digital media file **60** may be transmitted, i.e., “pushed” or “pulled”, between the media node **30** and the media terminal **20**, as shown at **110**.

More in particular, because the digital media file **60**, for purposes of the illustrative implementation shown in FIG. 4, is initially disposed on the media node **30**, the digital media file **60** may be transmitted, i.e., “pushed” or “pulled”, to the media terminal **20** from the media node **30** via the communication link **70**. In particular, the media terminal **20** may display the digital media file **60**, save the digital media file **60**, and/or manipulate or edit the digital media file **60**. In addition, the media terminal **20**, in at least one embodiment, may be structured to transmit the digital media file **60** and/or the edited media file back to the media node **30** via the communication link **70**.

~~Since many modifications, variations and changes in detail can be made to the system as present herein, it is intended that all matters in the foregoing description and shown in the accompanying drawings be interpreted as illustrative and not in a limiting sense. Thus, the scope of the present system should be determined by the appended claims and their legal equivalents. Now that the invention has been described,~~